



FLIR Scout Pro



FLIR Scout Pro II



FLIR Scout Pro III

Key Features

- Wireless video streaming functionality through Scout Pro App
- Easy to use menu, requires minimal training
- Rugged and reliable with IP67 rating and 2 m drop protection
- Fixed focus (Scout Pro) convenient for intense usage, manual focus (Scout Pro II and III) for flexibility

Main Applications

- First Responders
- Surveillance
- Evidence Gathering
- Active Pursuit



SPECIFICATIONS

	FLIR Scout Pro	FLIR Scout Pro II	FLIR Scout Pro III
Product name	Scout Pro	Scout Pro II	Scout Pro III
Part No.	15001-0101	15002-0101	15003-0101
Field of view	32°	18°	12°
Focal length	19 mm	35 mm	50 mm
F-number	f/1.0	f/1.0	f/1.1
Focus	Fixed focus	Manual focus	Manual focus
Human detection range	500 m (550 yds)	1000 m (1100 yds)	1500 m (1600 yds)
Minimum near focus distance	4 m (13 ft)	2 m (6 ft 7 in)	3 m (9 ft 10 in)
Frame rate	30 Hz		
Display frame rate	60 Hz		
Spectral range	7.5 – 13.5 µm		
Pixel pitch	17 µm		
Thermal sensitivity, NETD	<38 mK @ 30°C (86°F)		
Resolution	640 × 480 Vox Microbolometer		
Image processing	FLIR DDE 2.0		
User interface			
Zoom	2x, 4x 6x, 8x		
Color palettes	White Hot, Black Hot, Sepia, Heat		

Image presentation			
Built-in display	XGA 1024 × 768		
Video	XGA 1024 × 768		
Power			
Battery life	Up to 6 h		
Battery type	Internal Li-ion cell		
Charging time	2 h 80% capacity		
Physical			
Color (housing)	Black		
Drop rating	2 m (6 ft 7 in)		
IP rating	IP67, 1/2 hour submersible under 1 m		
Operating temperature	-15°C to 45°C (5°F to 113°F)		
Size (L × W × H)	19.2 × 6.4 × 6.4 cm (11 × 6 × 3 in)	21.2 × 6.4 × 6.4 cm (8.33 × 2.51 × 2.51 in)	23.2 × 6.4 × 6.4 cm (8.33 × 2.51 × 2.51 in)
Weight (incl. battery)	498 g (1.098 lbs)	660 g (1.455 lbs)	745 g (1.642 lbs)
Tripod mounting	UNC 1/4"-20	UNC 1/4"-20	UNC 1/4"-21
Communication & Storage			
Media gallery	Scout Pro App (iOS and Android)		
Storage media	Embedded flash		
Image modes	IR		
File formats	Standard JPEG		
Video recording	Yes		

Specifications subject to change. For the most up-to-date specifications, please visit flir.com.

SPECIFICATIONS, CONT.



	FLIR Scout Pro	FLIR Scout Pro II	FLIR Scout Pro III
Non-radiometric IR video recording		MPEG4 AVC (ITU-T H.264)	
Storage capacity		16 GB	
Video streaming		Yes	
Non-radiometric IR video streaming		WiFi/RTSP (MPEG4 AVC (ITU-T H.264))	
USB streaming		UVC (YUV422 no overlay)	
Wireless connectivity			
Bluetooth		BLE	
Streaming		Wi-Fi	

Specifications subject to change. For the most up-to-date specifications, please visit flir.com.

HUMAN SIGNATURE DETECTION RANGE



Ranges calculated using Johnson criteria



For technical or sales support, please visit:
www.flir.com/about/general-inquiries

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com. ©2025 Teledyne FLIR, LLC. All rights reserved.

Revised 09/10/25
FLIR_ScoutProSeries_Datasheet_en-US-ITR_25-0654-INS