



# TECHNICAL SHEET

FA 30 400 18

**Designation:**

Forked energy absorbing webbing lanyard

- Energy absorber in 35 mm wide webbing which reduces the impact of the fall to less than 6 kN.
- 30 mm wide polyester webbing lanyard.
- Loops protected by an abrasion resistant tubular webbing.

**Connectors:**

2 scaffold hooks, opening 55 mm, ref. FA 50 207 55 and 1 screw-locking karabiner opening 17 mm, ref. FA 50 101 17.

**Compliance:**

EN355:2002 and tested as per VG11 of PPE Directive 89/686/CEE

**Length:**

Lg : 1.8 mtr (connectors included)

**Materials:**

Lanyard: polyester

Absorber: polyester and polyamide

Connectors: steel



**HS code**

56090090

**Carton Size / Pieces**

47x36x26 / 10

**Unit Weight**

1.65 kg

**AET: N° 4302 Issue 3 Extension 1**

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering,  
Northamptonshire, NN16 8SD, United Kingdom.

**Article 11: GB07/73551**

SGS United Kingdom Ltd., N° 0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 04/14

**ZI les portes du Dauphiné**

**4 rue de l'Aigue**

**69 780 St Pierre de Chandieu – France**

**Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32**

**www.kratossafety.com info@kratossafety.com**

