



TECHNICAL SHEET

FA 30 503 15

Designation :

Energy Absorbing Kernmantle Rope Lanyard composed of :

- Energy absorber in 44 mm wide webbing which reduces the impact of the fall to less than 6 kN
- 12 mm diam polyamide Kernmantle rope lanyard
- Loops protected by an abrasion resistant thimble
- Sewing protected with strong transparent covering sleeve.

Connectors :

1 connector double action with automatic locking, opening 17 mm, reference FA5020217 and 1 scaffold hook double action with automatic locking, opening 55 mm, reference FA5020755

Compliance :

EN355 : 2002 and tested as per VG11 - 89/686/EEC



Length :

Lg : 1,5 m (connectors included)

Materials :

Lanyard : polyamide

Absorber : polyester et polyamide

Connectors : steel

HS code

56090090

Carton Size / Pieces

60x40x24 / 25

Unit Weight

1,16 kg

AET : N° 4334 Issue 2 Extension 5

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11 : GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



maj : 03/12

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

