



TECHNICAL SHEET




FA 20 400 15

Designation: Retractable Fall Arrester Olympe in wire rope

- Steel wire rope diam. 4.8 mm.
- Casing made up of high impact strength Polymer to prevent breakage and nearly indestructible.
- Swivel at the top and at the bottom of the device.
- Lateral carrying handle.
- Minimum breaking strength: > 12kN.
- Rubber protective snout for manipulating the cable.

Connectors: 1 screw-locking karabiner, opening 17 mm, ref. FA 50 101 17 et 1 snap hook with swivel and fall indicator, opening 21 mm.

Compliance: Conforms to EN360:2002.
 Certified for a horizontal use when used with the lanyard ref. FA 40 304 15 connected to the wire rope of the block.



Length: 15 mtrs.

Material of the components:

Polymer casing: PA 6 30% fiberglass.
 Wire rope: Galvanized steel.
 Connectors: Steel.

HS code	Carton size / Pieces	Unit weight
84289090	60x40x24 / 2	6.80 Kg

AET : N° 4023 Issue 4 Extension 2

Satra Technology Centre, N°0321
 Wyndham Way, Telford Way, Kettering,
 Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
 Unit 202B, Worle Parkway,
 Weston-super-Mare, BS22 6WA, United Kingdom



ZI les portes du Dauphiné
 4 rue de l'Aigue
 69 780 St Pierre de Chandieu – France
 Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32
 www.kratossafety.com info@kratossafety.com

