

**Designation :** Olympe Retractable Fall Arrester in wire rope with Rescue Winch

- Galvanized steel wire rope diam. 4,5 mm.
- High impact strength Polymer casing, to prevent breakage.
- Swivel at anchorage end and on the karabiner at attachment end.
- Minimum breaking strength : > 12 kN.
- Integrated recovery system, the device can be adapted on our TRIPOD.

**Connectors:** 1 steel screw-locking karabiner, opening 17 mm, ref. FA 50 101 17 and 1 steel snap hook with swivel and fall indicator, opening 21.5 mm, ref. PN 162.

**Compliance:** Conforms with EN 360:2002 and EN 1496:2006 Class B.



**Length:** 30 mtrs.

**Materials:**

Protective casing: PA 6 30% fibreglass.  
Wire rope: Galvanized steel.  
Connector: Steel.

HS code	Carton Size / Pieces	Unit Weight
84289090	80x40x24 / 2	14.80 Kg

**AET : N° Issue Extension**

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering,  
Northamptonshire, NN16 8SD, United Kingdom.

**Article 11: GB07/73551**

SGS United Kingdom Ltd., N° 0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 12/14

**ZI les portes du Dauphiné**  
4 rue de l'Aigue

69 780 St Pierre de Chandieu – France  
Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32  
[www.kratossafety.com](http://www.kratossafety.com) [info@kratossafety.com](mailto:info@kratossafety.com)

