

7601.37

Portable Units



FEATURES & BENEFITS

Construction

Stainless steel constructed tank makes for a solid portable unit with added resistance against corrosion and breakage.

Flow Controls

Green ABS plastic Soft-Flo anti-surge heads and a Feather-Flo® head equipped with this 37 gallon portable unit distribute water at .25 gpm (2) for the eyewash and 4gpm for the drench hose when pressure is between 30 and 90 psi to provide a thorough irrigation process.

Valves

Eyewash valve comes equipped with stainless steel ball and stem for added protection against corrosion and breakage. Unit also comes with a chrome-plated brass squeeze valve supplied with a 6.25 gpm flow control.

Added Protection

Green polyethylene plastic dust covers that release with water pressure keep the unit protected from debris up until the last second before use further optimizing operation. The 6' hose extends the portable units reach and is pressure rated at 250 psi making for a better piece of emergency equipment.

Safety

Air pressure gauge, pressure relief valve, tire-type air fill valve, and supplied bottle of bacteriostatic additive decrease the possibility of mishaps and make for a safer piece of emergency equipment.



Model shown with optional model 9008 cart

SPECIFICATIONS

Model 7601.37 portable air pressure operated eyewash with body spray shall include a stainless steel 37-gallon ASME 130 psi rated tank, ABS plastic anti-surge eyewash heads with .25 gpm (2) flow controls and dust covers, chrome-plated brass stay-open ball valve equipped with stainless steel ball and stem, 160 psi air pressure gauge, 110 psi air pressure relief valve, and tire-type air fill valve. Unit shall also include squeeze-valve operated body spray, label-mounted operating instructions, and 1 bottle of bacteriostatic additive to permit storage of water for six months.

OPTIONS

- Bacteriostatic Additive: Model 9082, bacteriostatic preservative for use in portable eyewash stations. One 8 oz. (237 ml) bottle will preserve 6 to 20 gallons of portable water for up to six months. Four bottles per carton.
- Cart: Model 9008 cart is designed to transport models 7601.37, 7500, or 7501 portable eyewashes, and the 9009 wastewater container. Unit is constructed of heavy-duty 1" tubular frame with green powder-coated finish and equipped with four solid rubber wheels.

APPLICATIONS

Where the eyes of any person may be exposed to injurious or corrosive materials, when suitable facilities for quick flushing of the eyes needs to be provided and a continuous supply of water is not available. Although the 7601.37 may be used in a wide variety of locations, it is ideal for the remote and low traffic areas where protective and mobile measures may still be needed. Emergency eyewash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7601.37 is certified by CSA & IAPMO to meet the ANSI Z358.1-2004 Standard for Emergency Eyewash and Shower Equipment.

