

FABIO S3 HIGH



STANDARD EN ISO 20345 : 2011




LEMAITRE

Safety since 1974






CARBON
by LEMAITRE



Carbon fiber toe-cap
Cutting-edge technology from
the aeronautical industry

Sizes 35 to 49 Reference code: FABIS30BE

Product Highlights

-  **Carbon toe-cap by Lemaitre** : ergonomic build, lightness, similar resistance to steel, athermic and non-magnetic
- Memory Foam insole by Lemaitre**: anti-bacterial memory structure, odor neutralizer, MSDs prevention
- Microfiber upper and retro-reflective side marker**: enhanced visibility. Lightness, breathability and resistance to tearing and abrasion
- Bellows Tongue**: to limit intrusion of dust and stones
- Reinforced abrasion-resistant cap, increased resistance
-  **Protective toe-cap**: Carbon by Lemaitre
-  **Puncture resistant midsole**: high tenacity fabric "0" penetratio



Anti-static sole CARBON PU2D

- Developed outsole for industrial and urban floors
- Large bearing surface**: optimal stability
- Shock absorption**: preservation of the back and joints
- Conformal to bent positions**: knee notches and crouching
- Sculpted studs**: reinforced grip

USAGE

- Finishing works, light industry, logistics, services, handling



lemaitre-secureite.com

An exacting attitude to quality is our culture, safety our priority



FABIO S3 HIGH



STANDARD EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material** : water-repellent microfiber with an abrasion-resistant cap in "groove"
- **Bellows tongue**: abrasion-resistant textile
- **Collar** : abrasion-resistant textile
- **Lining**: 3D microporous fabric

Characteristics of the sole

- **Designation** : CARBON PU2D
- **Material** : polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient** :
forward flat slip: 0,34 (standard ≥ 0,32)
forward heel slip: 0,31 (standard ≥ 0,28)
- **SRB Adhesion coefficient** :
forward flat slip: 0,22 (standard ≥ 0,18)
forward heel slip: 0,20 (standard ≥ 0,13)

VARIANT



Flavio S3 SRC
FLAVS30BE

Practical information

Weight of one shoe size 42 : 530 g

CERTIFICATION N° IN PROCESS

Packaging

sizes 35 to 42

shoebox 315 x 220 x 123 mm

carton 635 x 445 x 315 mm

10 shoeboxes per carton

sizes 43 to 49

shoebox 355 x 220 x 130 mm

carton 660 x 450 x 360 mm

10 shoeboxes per carton

Gencods

35	3237154303351	43	3237154303436
36	3237154303368	44	3237154303443
37	3237154303375	45	3237154303450
38	3237154303382	46	3237154303467
39	3237154303399	47	3237154303474
40	3237154303405	48	3237154303481
41	3237154303412	49	3237154303498
42	3237154303429		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP			
S1			(A) (E) (Fo)
S1P			(A) (E) (Fo)
S2			(A) (E) (Fo) (Wru)
S3			(A) (E) (Fo) (Wru)

200 J toe-cap: protection of the forefoot against impact and crushing

Anti-perforation insert 1100 N: foot protection against perforation

(A)	Anti-static footwear	(Ci)	Insulation against cold
(E)	Shock absorption at the heel	(Hi)	Insulation against heat
(Fo)	Fuel oil-resistant outsole	(Hro)	Outsole resistance to hot contact
(Wru)	Water penetration and water absorption resistant upper	(Wr)	Water resistant
	Electrostatic discharge	(An)	Ankle protection
△ SRA	Slip-resistance on ceramic floors with detergent		
△ SRB	Slip-resistance on steel floors with glycerol		
△ SRC	= △ SRA + △ SRB		

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com



DON_LS 04 TDS 0020
Update : 10/03/20

Member of
SYNAMAP

