TECHNICAL DATA SHEET



LEMAITRE SÉCURITÉ S.A.S. B.P. 90024 17, route de Bitschhoffen 67350 La Walck - France Tel: +33.388.72.28.80 Fax: +33.388.07.05.37 www.lemaitre-securite.com



CELINE S2 CI

<u>Sizes</u> EU : 35 to 42 UK/AU/NZ : 2 to 8

Description CAMPER STYLE LOW CUT SHOE WITH WATER-RESISTANT NUBUCK LEATHER

UPPER specifications

Leather	Water-resistant full-grain nubuck
	leather 1.6-1.8mm thick
Tongue	Water-resistant full-grain leather
Collar	Latex foam
Lining	Cambrelle®
Heel stiffener	Synderme
Fastening	Lacing strip
Laces	Polyamide, resistant to abrasion
	(> 15000 frictions under 250g
	according to norm DIN4843)

FITTING specifications

Last	Wide fitting, according to
	Natur'Form concept
Тое сар	Wide ABG toe cap, 200 joules
•	according to norm EN 345-1

SOLE specifications

Construction	California.
Insole	Antistatic Texon 2.0mm thick
Arch support	Polyethylene anatomic insock
	with integrated arch support
Sole material	Dual-density polyurethane
	 midsole density: 0,50
	 outsole density: 1,00
Sole resistance	Oil and acid resistant
	Heat resistance up to 180°C

Advantages

- Water-resistant nubuck leather
- Protection of malleolus
- Cambrelle[®] lined for more comfort
- Cold insulation of sole complex (CI)
- "City" look, can be worn in all circumstances
- Integrates safety and good look
- <u>Sole with Parabolic profile</u>[®]: the concave structure of allows a progressive deforma-tion of the sole in order to optimize the grip to industrial floors
- <u>Exceptional slip resistance</u>: the footprint adapts itself to the nature of the ground due to the profile of the sole
- Slip resistance coefficient : 0.19
- <u>Spring effect</u>: gives a more dynamic walk
- Sizes: 35 42 / 2 8

Protection

- According to norms EN 344-1 and EN 345-1
- Toe cap: 200 joules
- <u>S2</u>: basic requirements + closed back + antistatic + energy absorption at heel + oil resistance of outsole + cleated outsole + water-resistant upper

<u>Weight</u>

350g / 12.3oz per foot (for size 38/5, ± 5%)

European standard : CE certificate N°: 0075/007/161/11/01/104 - Ext. N° 10/11/01. This product has been subjected to CE type approval tests made by a notified body according to norms EN 344-1 and EN 345-1.	CE	LEMAITRE SÉCURITÉ is certified ISO 9001 : 2000
		AF
Markings (on tongue): Size, manufacturer's identification, identification of mod of manufacture, reference of applicable standard, type of protection, CE mark.		