

DESERT S3



Standard EN ISO 20345 : 2011

LEMAITRE

Safety since 1974



Stainless steel anti-perforation insert

Exceptional puncture resistance

+ 80% performance compared to textile insert

Sizes 35 to 49

Ref. DESES30BFSN

Product Highlights



■ Heavy duty boot available with men's and women's fit.



■ 2,0 mm thick high strength leather (against abrasion, tearing and puncture).

■ Reinforced anti-abrasion overcap for long-lasting durability

■ Lining in 3D microporous fabric, ventilation inside the shoe, comfort



■ Side ties and TPU protection at the back to facilitate the donning and doffing of boots

■ Anatomical and antibacterial Energy+ insock: impact reduction, odor neutralization.



■ Protective toe-cap: composite HDFC.



■ Puncture-resistant midsole: stainless steel



Antistatic TRAILIUM PU2D Outsole

■ 4 mm studs suitable for construction and heavy duty industry

■ Drainage channels for liquids and mud to avoid any risk of aquaplaning

■ Lateral edges and 15mm raised heel: reinforced grip on ladder rungs

■ Large bearing surface, optimal stability

■ Arch support and heel cushioning: MSD prevention


USE

- Construction, heavy industry
- Outdoor activities



lemaitre-securite.com

Lemaitre takes care.



DESERT S3



Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** water-repellent oiled split leather with anti-abrasion/anti-wear groove scuffcap
- **Lining:** 3D microporous fabric
- **Side ties:** water-repellent oiled split leather

Characteristics of the sole

- **Designation :** TRAILIUM PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,35 standard $\geq 0,32$
forward heel slip: 0,38 (standard $\geq 0,28$)
- **SRB Adhesion coefficient:**
forward flat slip: 0,19 (standard $\geq 0,18$)
forward heel slip: 0,17 (standard $\geq 0,13$)

VARIANT



Transalp S3 SRC
TRANS30BFSN

Practical information

Women fitting 35-39

Weight of one shoe size 38:
740 g

AET N°

075/007/161/07/19/2226 E
10/03/20

Men fitting 40-49

Weight of one shoe size 42:
820 g

AET N°

0075/007/161/07/19/2226
EXT 11/03/20

Packaging

sizes 35 to 49

shoobox 350 x 340 x 130 mm

carton 670 x 355 x 360 mm

5 shoeboxes per carton

Gencods

35	3237154138359	43	3237154138434
36	3237154138366	44	3237154138441
37	3237154138373	45	3237154138458
38	3237154138380	46	3237154138465
39	3237154138397	47	3237154138472
40	3237154138403	48	3237154138489
41	3237154138410	49	3237154138496
42	3237154138427		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP						
S1			(A)	(E)	(Fo)	
S1P			(A)	(E)	(Fo)	
S2			(A)	(E)	(Fo)	(Wru)
S3			(A)	(E)	(Fo)	(Wru)

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

(A)	Anti-static footwear	(Ci)	Insulation against cold
(E)	Shock absorption at the heel	(Hi)	Insulation against heat
(Fo)	Fuel oil-resistant outsole	(Hro)	Outsole resistance to hot contact
(Wru)	Water penetration and water absorption resistant upper	(Wr)	Water resistant
	Electrostatic discharge	(An)	Ankle protection

SRA Slip-resistance on ceramic floors with detergent

SRB Slip-resistance on steel floors with glycerol

SRC = **SRA** + **SRB**

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE
Safety since 1974

Member of
SINAMAP



DON_LS 04 TDS 0171
update: 13/02/2024