


CHUKKA NOIR S3 SRC



Standard EN ISO 20345 : 2011

LEMAITRE

Safety since 1974



memoryfoam By LEMAITRE

- 100% high density recycled foam



Sizes 38 to 50

Réf. CHUKS30NR

Product Highlights

- Upper in water-repellent suede microfiber : lightness, breathability, tearing and abrasion resistant

Breathable perforated microfiber lining: anti-allergic and anti-microbial, thermoregulatory effect. Prevents odor formation.

Memory Foam by Lemaître anti-bacterial insole with memory foam, energy absorption and dissipation, MSD prevention

Derby shoe characterized by open lacing: easy to put on, adapts to the morphology of the foot. Good hold, comfort. Suitable for strong instep

Casual chic style: elegance and relaxation, a great classic of the city shoe revisited as a safety shoe.



- Protective toe cap:** HDPC composite fiber.



- Anti-perforation insert:** high tenacity composite textile «0» penetration.



Anti-static sole CARBON PU2D

Developed outsole for industrial and urban floors: good adhesion

Large bearing surface: optimal stability

Shock absorption: preservation of the back and joints

Conformal to bent positions: knee notches and crouching

Sculpted studs: reinforced grip

USE

- Service company, crafts, management.
- Logistics, services, handling, distribution, transportation.



lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority



CHUKKA NOIR S3 SRC



Standard EN ISO 20345 : 2011

Characteristics of the upper

Upper material : water-repellent microfiber velvet effect

- **Tongue :** water-repellent microfiber
- **Lining :** smooth perforated microfiber

Characteristics of the sole

Designation: CARBON PU2D

- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,34 (standard \geq 0,32)
forward heel slip: 0,31 (standard \geq 0,28)
- **SRB Adhesion coefficient:**
forward flat slip: 0,22 (standard \geq 0,18)
forward heel slip: 0,20 (standard \geq 0,13)

VARIANT



Chukka noir O2 SRC
CHUKO20NR

Practical information

Weight of one shoe size .42 : g

AET N° 0075/007/161/09/19/2718 EXT 24/12/22

Packaging

Size 38 to 43

shoebox 316 x 204 x 121 mm

carton 635 x 445 x 325 mm

10 shoeboxes per carton

Size 44 to 50

shoebox 355 x 220 x 130 mm

carton 635 x 485 x 355 mm

10 shoeboxes per carton

Gencods

38 3237154507384

39 3237154507391

40 3237154507407

41 3237154507414

42 3237154507421

43 3237154507438

44 3237154507445

45 3237154507452

46 3237154507469

47 3237154507476

48 3237154507483

49 3237154507490

50 3237154507506

Memo for basic and additional requirements of the standard EN ISO 20345 : 2011

Safety footwear

SBP						
S1			A	E	Fo	
S1P			A	E	Fo	
S2			A	E	Fo	Wru
S3			A	E	Fo	Wru

200 J toe cap: Protection of the forefoot against shocks and crushing

Anti-perforation insert 1100 N: foot protection against

A	Anti-static footwear	Ci	Insulation against cold
E	Shock absorption at the heel	Hi	Insulation against heat
Fo	Fuel oil-resistant outsole	Hro	Outsole resistance to hot contact
Wru	Water penetration and water absorption resistant upper	Wr	Water resistant
	Electrostatic discharge	An	Ankle protection

SRA Slip-resistance on ceramic floors with detergent

SRB Slip-resistance on steel floors with glycerol

SRC = **SRA** + **SRB**