

TECHNICAL FILE

UPDATEMENT of the document : 22/09/2011
Reference of the document: DON/LS 03.1084.A



LEMAITRE SECURITE SAS
17 rue Bitschhoffen
BP 90024
F 67350 La Walck FRANCE
Tél. : +33 (0)3 88 72 28 80
Fax : +33 (0)3 88 07 05 37
www.lemaitre-securite.com
info@lemaitre-securite.com



Ankle shoe in leather

SMARTFOX HIGH S1P



Sizes available from 39 to 48
Weight of one pair in size 42 : 1170 gr.
Norm EN ISO 20345 : 2007
AET : in process

Upper features

- Upper : leather
- Collar : synthetic
- Tongue : synthetic
- Lining : textile
- Vamp lining : synthetic
- Counter : leather board
- Eyelet : metallics
- Laces : polyamide
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

Protections

- Toecap : steel (200 joules)
- Midsole : stainless steel anti-perforation insert

Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : textile
- Footbed : polyurethane

Sole features

- Name : NE - 10
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Undermine sole density : 1
- Undermine sole color : light grey
- Slip resistance SRA (flat) : 0.50
- Slip resistance SRA (heel) : 0.39
- Slip resistance SRB (flat) : 0.21
- Slip resistance SRB (heel) : 0.15

Requirements of the norm EN ISO 20345 : 2007

	Steel toecap		Polycarbonate toecap		Aluminum toecap (200 joules)
	Steel midsole		Non metallic midsole		
	A	A Electric resistance – Antistatic shoes.			
	Ci	Ci Insulating sole against cold.			
	E	E Heel energy absorption.			
	Fo	FO Hydrocarbons resistance of the undermine sole.			
	Hi	HI Insulating sole against heat.			
	Hro	HRO Heat resistance of the sole.			
	M	M Metatarsal protection.			
	P	P Perforation resistance.			
	Wru	WRU Water repellent upper.			
	Wr	WR Water repellent junction upper/sole.			



Regarding the norm EN ISO 20345 : 2007, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) = 0,32
SRA (heel) = 0,28
SRB (flat) = 0,16
SRB (heel) = 0,12

Advantages = End users benefits

2,2mm thickness leather for better resistance (to abrasion and tearing) and longer durability.

NE – 10 sole :

- Attack heel, for a natural unfolding of the foot during walking and comfort while driving vehicle
- Dual density polyurethane (PU / PU or PU2D) injected for better resistance and comfort
- High profile heel for better safety
- Heel shock absorber
- Non-slip structure with a studded open for better drainage of fluids
- Ideal for industrial floors and tough environments