

# FLAVIO S3



STANDARD EN ISO 20345 : 2011


## LEMAITRE

Safety since 1974



### CARBON

by LEMAITRE




Carbon fiber toe-cap  
Cutting-edge technology from  
the aeronautical industry

Sizes 35 to 49

Ref. FLAVS30BE

## Product Highlights

-  **Carbon toe-cap by Lemaître:** ergonomic build, lightness, similar resistance to steel, athermal and non-magnetic
- Memory Foam insole by Lemaître:** antibacterial memory structure, odor neutralizer, MSDs prevention
- Microfiber upper and retro-reflective side marker:** enhanced visibility. Lightness, breathability and resistance to tearing and abrasion
- Bellows tongue:** to limit intrusion of dust and stones, reinforced abrasion-resistant cap, increased resistance
- Reinforced abrasion-resistant cap,** increased resistance



- Protective toecap:** Carbon by Lemaître



- Puncture resistant midsole:** high tenacity fabric «0» penetration



## Anti-static sole CARBON PU2D

- Developed outsole for industrial and urban floors**
- Large bearing surface:** optimal stability
- Shock absorption:** preservation of the back and joints
- Conformal to bent positions:** knee notches and crouching
- Sculpted studs:** reinforced grip

## USE

- Finishing works, light industry, logistics, services, handling



[lemaitre-securite.com](http://lemaitre-securite.com)

An exacting attitude to quality is our culture, safety our priority



# FLAVIO S3



STANDARD EN ISO 20345 : 2011

## Characteristics of the upper

- **Upper material:** water-repellent microfiber with an abrasion-resistant cap in «groove»
- **Bellows tongue:** abrasion-resistant textile
- **Collar:** abrasion-resistant textile
- **Lining:** 3D microporous fabric

## Characteristics of the sole

- **Designation:** CARBON PU2D
- **Material:** polyuréthane / polyuréthane
- **Antistatic sole**
- **SRA Adhesion coefficient:**  
forward flat slip: 0,34 (standard ≥ 0,32)  
forward heel slip: 0,31 (standard ≥ 0,28)
- **Coefficient d'adhérence SRB :**  
forward flat slip: 0,22 (standard ≥ 0,18)  
forward heel slip: 0,20 (standard ≥ 0,13)

## VARIANT



**Fabio S3 SRC**  
FABIS30BE

## Practical information

Weight of one shoe size.42 : 515 g

AET N° 0075/007/161/09/19/2718 EXT 11/03/20

## Packaging

### Sizes 35 to 42

**shoebox** 315 x 220 x 123 mm

**carton** 635 x 445 x 315 mm

10 shoeboxes per carton

### Sizes 43 to 49

**shoebox** 355 x 220 x 130 mm

**carton** 660 x 450 x 360 mm

10 shoeboxes per carton

## Gencods

<b>35</b>	3237154302354	<b>43</b>	3237154302439
<b>36</b>	3237154302361	<b>44</b>	3237154302446
<b>37</b>	3237154302378	<b>45</b>	3237154302453
<b>38</b>	3237154302385	<b>46</b>	3237154302460
<b>39</b>	3237154302392	<b>47</b>	3237154302477
<b>40</b>	3237154302408	<b>48</b>	3237154302484
<b>41</b>	3237154302415	<b>49</b>	3237154302491
<b>42</b>	3237154302422		

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP



S1



S1P



S2



S3



200J toecap: protection of the forefoot against impact and crushing



Anti-perforation insert 1100 N: foot protection against perforation



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



SRC = SRA + SRB

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE

Safety since 1974

DON\_LS04TDS0021  
Update : 10/03/20

Member of  
SYNAMAP

