

## TECHNICAL DESCRIPTION

<b>STYLE</b>	<b>D223 S2</b>
<b>ARTICLE</b>	DERBY SHOE S2
- sizes	35-47
- colour	black
- weight one pair	kg 0,920 size 42 (without toecap 0,760)
<b>SOLE</b>	Polyurethane monodensity antistatic, anti-slip, resistant to oils and acids, injected, colour black
- antistaticity	9,15 x 10 (7) Ohm
- antislip resistance	to ENV 13287 (00) coefficient 0,25
<b>UPPER</b>	LORISAFE waterproof
- water vapour perm.	2,0 mg/cm <sup>2</sup> x h
<b>COLLAR PADDING</b>	Synthetic sponge of 5 mm
<b>STROBEL</b>	Woven-unwoven fabric colour grey
<b>VAMP LINING</b>	Woven-unwoven felt, high sweat absorption, high perspiration, colour grey
<b>COUNTER LINING</b>	“Cambrelle” with Mtp, smooth, high perspiration
- water vapour perm.	5,0 mg/cm <sup>2</sup> x h
<b>INSOLE</b>	Full latex insole antistatic anti-bacterial, anti-mouldy, “Cambrelle“ covered, colour grey
<b>TONGUE</b>	LORISAFE waterproof
<b>COUNTER</b>	Salpa
<b>LACES</b>	Special for safety shoes
<b>CLOSING SYSTEM</b>	4 plastic eyelets pairs
<b>STEEL TOECAP</b>	To EN 345 resistant to 200 J, anti-rust painted
<b>TOECAP PADDING</b>	Anatomic synthetic padding
<b>MARKING</b>	EN 345-1 S2
<b>PACKAGING</b>	Ecological paper, 1 pair/box Safe Way
- box-end-label	10 prs/size/carton
- information sheet	design of the style, size, colour, bar code, Standard
- tissue paper	in every box Safe Way