

# Superfood 175

## DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex
- **Length (cm)** 31
- **Thickness (mm)** 0.40
- **Wrist** Straight cuff
- **Colour/Color** Blond
- **Interior finish** Smooth
- **Exterior finish** Embossed texture, chlorinated
- **Size / EAN** 6 7 8 9 10
- **Packaging** 1 pair/bag - 10 pairs/box - 100 pairs/carton
- **Complementary information** Guaranteed without silicone



## PERFORMANCE RESULTS

Certification category 3

CE 0334



0010

### Legends



**MECHANICAL HAZARDS**  
EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4  
 └─ Puncture resistance  
 └─ Tear resistance  
 └─ Blade cut resistance  
 └─ Abrasion resistance



**LOW CHEMICAL PROTECTION**  
EN 374



**MICRO-ORGANISMS**  
EN 374



**RADIOACTIVE CONTAMINATION**  
EN 421



**HEAT AND FIRE**  
EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4  
 └─ Resistance to large quantities of molten metal  
 └─ Resistance to small drops of molten metal  
 └─ Radiant heat resistant  
 └─ Convective heat resistance  
 └─ Contact heat resistance  
 └─ Burning behaviour



**SPECIFIC CHEMICAL PROTECTION**  
EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS**  
EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1  
 └─ Water permeability  
 └─ Contact cold resistance  
 └─ Convective cold resistance

For more details: [www.mapa-pro.com](http://www.mapa-pro.com)

# Superfood 175

## DESCRIPTION AND GENERAL PROPERTIES

- Excellent dexterity: a thin glove in a supple material
- Chlorinated finish for better protection of products being handled

## MAIN FIELDS OF USE

### Mechanical industry

- Assembly of small, oil and grease free parts

### Food industry

- Common cleaning Tasks

### Local Authorities (Cleaning)

- Handling household detergents

## INSTRUCTIONS FOR USE

### Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at the workplace may differ from the «CE»-type tests.
- It is not recommended for persons sensitized to natural latex, dithiocarbamates and thiazoles to use this gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website [www.mapa-pro.com](http://www.mapa-pro.com) or contact the Technical Customer Service - MAPA PROFESSIONNEL ([stc.mapaspontex@mapaspontex.fr](mailto:stc.mapaspontex@mapaspontex.fr)) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.

Inspect the gloves for cracks or snags before reusing them.

### Storage conditions

Store the gloves in their original packaging, protected from direct sunlight, far from heat sources or electric equipment.

### Laundering conditions

Before taking off the gloves, clean them as appropriate :

- in use with a solvent (alcohol, etc...) : rub over with a dry cloth
- in use with detergents, acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth. Caution: Inappropriate usage of the gloves or submitting them to a cleaning or laundering process which is not specifically recommended can alter their performance levels.

### Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

## LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

• CE-Type Examination Certificate  
0075/014/162/04/10/0141 Ext 02/04/10

• Issued by the notified body nr  
0075

C.T.C. – 4, rue Hermann Frenkel - 69367 Lyon cedex 07- France

• Quality assurance certificat  
0334 Asqual 14 rue des Reculettes -F-75013 PARIS