

Vital 520

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex
- **Length (cm)** 33
- **Thickness (mm)** 0.40
- **Wrist** Straight cuff
- **Colour/Color** White
- **Interior finish** Powdered
- **Exterior finish** Smooth
- **Size / EAN** 6 7 8 9
- **Packaging** 1 pair/bag - 10 pairs/bag - 100 pairs/carton
- **Complementary information** - Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 3

CE 0334



Dexterity EN 420 : 5/5

KMP

2010X

Legends

ANSI	CUT RESISTANCE		
A1	A1 ≥ 200 G	A4 ≥ 1500 G	A7 ≥ 4000 G
	A2 ≥ 500 G	A5 ≥ 2200 G	A8 ≥ 5000 G
CUT	A3 ≥ 1000 G	A6 ≥ 3000 G	A9 ≥ 6000 G

EN 511	COLD HAZARDS		
	PERFORMANCE LEVELS		
	0-4	0-4	0 or 1
	└ Water permeability		
	└ Contact cold resistance		
	└ Convective cold resistance		

EN 407	THERMAL RISKS		
	Heat and fire		
	PERFORMANCE LEVELS		
	0-4	0-4	0-4 0-4 0-4 0-4
	└ Resistance to large quantities of molten metal		
	└ Resistance to small drops of molten metal		
	└ Radiant heat resistant		
	└ Convective heat resistance		
	└ Contact heat resistance		
	└ Burning behaviour		

PROTECTION FROM PESTICIDES

ISO 18889	ISO 18889	ISO 18889
G1	G2	GR

MICRO-ORGANISMS

EN ISO 374-5	EN ISO 374-5
Protection against bacteria, fungi	Protection against bacteria, fungi, virus
	VIRUS

CHEMICAL RISKS

EN ISO 374-1	EN ISO 374-1	EN ISO 374-1
Type A	Type B	Type C
U V W X Y Z	X Y Z	
A Methanol	J n-Heptane	
B Acetone	K Sodium hydroxide 40%	
C Acetonitrile	L Sulphuric acid 96%	
D Dichloromethane	M Nitric acid 65%	
E Carbon Disulfide	N Acetic acid 99%	
F Toluene	O Ammonia 25%	
G Diethylamine	P Hydrogen peroxide 30%	
H Tetrahydrofurane	S Hydrofluoric acid 40%	
I Ethyl acetate	T Formaldehyde 37%	

RADIOACTIVE CONTAMINATION



ELECTROSTATIC DISCHARGE PROTECTION



EN 388 MECHANICAL HAZARDS

EN 388	MECHANICAL HAZARDS		
	PERFORMANCE LEVELS		
	0-4	0-5	0-4 0-4 A-F (P)
	└ Impact protection		
	└ Cut resistance according to ISO 13997		
	└ Puncture resistance		
	└ Tear resistance		
	└ Blade cut resistance		
	└ Abrasion resistance		

For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONAL

SPECIFIC ADVANTAGES

- Excellent dexterity thanks to the flexibility of natural latex
- Smooth exterior finish provides greater protection for products being handled
- Previous name: Gantex 520

MAIN FIELDS OF USE

Local Authorities (Cleaning)

- Handling household detergents

Food industry

- Common cleaning Tasks
- Preparation and packaging

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- It is not recommended for persons sensitised to natural latex, thiurames, dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service -MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent. -These gloves are intended for protection against radioactive contamination by particules and are not designed to protect against ionizing radiation and for resistance to ozone cracking.They are not intended for containment enclosures against radioactive contamination.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

- Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in use with a solvent (alcohol, etc...) : rub over with a dry cloth,
- in use with acids or alkalies : thoroughly rinse the gloves under running water and rub over with a dry cloth.
- Caution : using the gloves or submitting them to another cleaning or laundering process can alter their performance levels .

Drying conditions

- Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/08/18/1649
- **Issued by the notified body nr** : 0075- CTC - 4 rue Hermann Frenkel - 69367 Lyon cedex 07 -France
- **Quality assurance certificat** : 0334 Asqual 14 rue des Reculettes -F-75013 PARIS