

ULTRANE 641





EN388

4121A

EN407

CAT.2

X1XXXX DEXTERITY

> EN 420: 5/5



Comfort, suppleness and high dexterity without any compromise on breathability and durability / Suitable for touchscreen

SPECIFIC ADVANTAGES

🕼 Comfort

• Comfort: high suppleness and flexibility, dexterity at fingertips.

Durability

• Extended use guaranteed by our exclusive process RESICOMFORT. Proven breathability, flexibility and durability of the coating.

Skin protection

- Free of harmful substances: STANDARD 100 by OEKO-TEX®, DMF Free
- Dermatologically approved

Suitable for touchscreen

• Can be used with touch devices & touch screen

👰 Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability

• Washable 1 time at 40°C without any alteration on performances*.

INDUSTRIES

- Automotive/mechanical industry
- Other industries
- Transport, logistics

APPLICATIONS

- Packaging
- Warehousing and receipt of goods
- Operating handling equipment
- Order preparation
- Assembly of small parts
- Automotive assembly
- Fitting small screws and fasteners
- Mechanical maintenance
- Precision assembly
- Precision mechanical work

Edit 20/12/2021

MAPA SAS capital de 35.000.010 € 420, rue d'Estienne d'Orves 92705 Colombes Cedex France RCS Nanterre 314 307 720 * Tests carried out on unworn gloves (i.e. in new condition) which differs from the reality in the field.



mapa-pro.com



ULTRANE 641

LEGENDS

| EN388 | MECHANICAL HAZARDS |
|-------------|---|
| Y | PERFORMANCE LEVELS (X = NOT TESTED) |
| 4 1 2 | <u>1</u> <u>A</u> <u>-</u> <u>P</u> |
| 0-4 0-5 0-4 | 0-4 A-F P Impact protection (optional) |
| | Cut resistance according to ISC 13997 |
| | Puncture resistance ar resistance t resistance ance |
| EN407 | THERMAL RISKS (HEAT AND FIRE) |
| ٢ | PERFORMANCE LEVELS (X = NOT TESTED) |
| X 1 X | XXX |
| 0-4 0-4 0-4 | X X X O-4 O-4 Resistance to large quantities of molten meta |
| | Resistance to small drops of molten metal |
| | Radiant heat resistant prvective heat resistance heat resistance viour |

(PRODUCT DETAILS)

| Interior finish | Seamless textile support |
|---------------------|--------------------------|
| Gauge | 15 |
| Exterior finish | Ventilated back |
| Material | Nitrile foam sandy |
| Cuff characteristic | Knitted Cuff |
| Colour.s | Black |
| Length (cm) | 22-27 |
| Size | 6 7 8 9 10 11 |

(LOGISTIC DETAILS)

| Packaging | 1 pair/bag 12 pairs/bag 96 pairs/carton | |
|-----------|---|--|
|-----------|---|--|

LEGISLATION

- $\,$ This product is not classified hazardous according to the regulation (EC) $\,$ n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/04/19/1047 Ext 01/06/20
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

Edit 20/12/2021

MAPA SAS capital de 35.000.010 €
420, rue d'Estienne d'Orves
92705 Colombes Cedex France
RCS Nanterre 314 307 720

