Allwork

DESCRIPTION

- · Industrial protective glove.
- · Model 'docker' in split leather.
- Rubberized cuff for added protection.
- 2 sizes available: 9 and 10.
- Trade unit: 10 pairs, 120 pairs in a transit case.

CHARACTERISTICS

- · Palm, full forefinger, finger tips in split leather.
- Thickness single wall: 1,20mm approximately.
- Reinforced back with elasticated band at the wrist.
- Inside palm liner with blue/yellow cotton striped back with inside elastic expander.

PERFORMANCES

- Good flexibility.
- · Good abrasion resistance and little cut.
- In compliance with EN420+A1 (General requirement) and EN388 (Mechanical hasards) by the notified laboratory SATRA Footwear Technology Centre.

APPLICATIONS

- · For general usage in dry environment.
- · Maintenance, forklift truck operator.

LIMITATIONS

• Do not use for handling liquids.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21rst, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.





EN 420+A1

2122

EN 388 Mechanical hazards EN 388

2 Abrasion

4 Dexterity

- 1 Cut
- 2 Tear
- 2 Puncture

Order codes

 Sizes
 9 (L)
 10 (XL)

 Allwork
 2210E03000
 2210E05000



