

ChemZoil 339

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Neoprene
- **Interior finish** Textile support
- **Exterior finish** Pebbled
- **Length (cm)** 35.5
- **Thickness (mm)** 1.35
- **Colour/Color** Black
- **Wrist** Scalloped cuff
- **Size** 9 10
- **Packaging** 1 pair/bag - 6 pairs/carton



PERFORMANCE RESULTS

Certification category 3

CE 0334



3221



ABCJKL



X1XXXX

Legends



MECHANICAL HAZARDS EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 Abrasion resistance
 Blade cut resistance
 Tear resistance
 Puncture resistance



LOW CHEMICAL PROTECTION EN 374



MICRO-ORGANISMS EN 374



RADIOACTIVE CONTAMINATION EN 421



HEAT AND FIRE EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 Burning behaviour
 Contact heat resistance
 Convective heat resistance
 Radiant heat resistant
 Resistance to small drops of molten metal
 Resistance to large quantities of molten metal



SPECIFIC CHEMICAL PROTECTION EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 Convective cold resistance
 Contact cold resistance
 Water permeability

For more details: www.mapa-pro.com

ChemZoil 339

SPECIFIC ADVANTAGES

- Superior chemical resistance against acids and alkalis, such as concentrated hydrofluoric acid, oils, and greases, due to its 100% neoprene multi-layer construction
- Pebbled embossing, for better grip on wet and slippery objects
- Excellent mechanical resistance and longer service life, due to the textile support and the thickness of the glove
- Thermal insulation from the cotton-knit lining for handling hot liquids

MAIN FIELDS OF USE

Chemical industry

- Handling and transporting drums of chemical products
- Handling on alkylation units
- Hot, petrochemical product sampling
- Resin-working
- Site pollution control

Mechanical industry

- Surface treatment of metals (acids)

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- Persons sensitized to dithiocarbamates should not use these gloves.
- Inspect the gloves for any defect before use.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dipping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

- Store the gloves in their original packaging at a temperature not below 5°C.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (diluents, etc...) : rub over with a dry cloth
- in use with acids and alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth
- Caution : improper use of the gloves or submitting them to another cleaning or laundering process which is not specifically recommended can alter their performance levels.

Drying conditions

- Ensure the inside of the gloves is dry before reusing them.

LEGISLATION

- This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- CE-Type Examination Certificate 0072/014/162/03/06/0018
- Issued by the notified body nr 0072
I.F.T.H. – Av. Guy de Collongue - F-69134 ECULLY CEDEX
- Quality assurance certificat O334 Asqual 14 rue des Reculettes -F-75013 PARIS