Temp-Ice 700

DESCRIPTION AND GENERAL PROPERTIES

- Material Nitrile GRIP&PROOF coating
- Length (cm) 24 to 27 cm
- Thickness (mm) Hvy. Wt.
- Wrist Knitted wrist
- Colour/Color Black / Blue
- Interior finish Knitted thermal protection
- Exterior finish Non-slip grip
- Size / EAN 7 8 9 10
- Packaging 1 pair/bag 12 pairs/bag 72 pairs/carton



PERFORMANCE RESULTS

Certification category 2







02X

3222

Legends **MECHANICAL** LOW CHEMICAL MICRO-ORGANISMS **RADIOACTIVE** PROTECTION CONTAMINATION **HAZARDS** EN 374 EN 388 EN 421 PERFORMANCE LEVELS 0-4 0-5 0-4 Puncture resistance SPECIFIC CHEMICAL **COLD HAZARDS** Tear resistance **PROTECTION** EN 511 Blade cut resistance EN 374 PERFORMANCE LEVELS -Abrasion resistance Letter Chemical 0-4 0-4 0 or 1 Code product Water permeability Methanol Contact cold resistance AND FIRE В Acetone Convective cold resistance EN 407 Acetonitrile D Dichloromethane PERFORMANCE LEVELS Carbon Disulfide 0-4 0-4 0-4 0-4 Toluene Resistance to large quantities of molten metal G Diethylamine Resistance to small drops of molten metal Tetrahydrofurane -Radiant heat resistant Ethyl acetate Convective heat resistance n-Heptane Sodium hydroxide 40% -Contact heat resistance Sulphuric acid 96% -Burning behaviour

For more details: www.mapa-pro.com



Temp-Ice 700

DESCRIPTION AND GENERAL PROPERTIES

- Coating 5 times as durable than standard gloves on the market
- Excellent grip when handling wet parts
- Stay dry when working in wet conditions
- Washable performances guaranteed after 5 cleaning cycles
- Suitable for frozen, dry and some fatty foods use according to the French law of November 9th, 1994 and to the European Directive CEE 1935/2004

MAIN FIELDS OF USE

Local Authorities (Catering Services)

Local Authorities (Roads and Highways)

· Maintaining the roads

Local Authorities (Parks and Public Spaces)

• Public park maintenance

Local Authorities (Waste Collection and Processing)

Waste collection

Other industries

- · Construction materials handling
- Maintenance in wet or cold environments

Transport, logistics

· Order preparation

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- It is not recommended for persons sensitised to natural rubber latex or dithiocarbamates to use these gloves.
- Put the gloves on dry, clean hands.
- Ensure the inside of the gloves is dry before putting them on again.
- The gloves may lose their insulating property in the wet state.

Storage conditions

Store the glove in their original packaging protected from heat, light and humidity.

Laundering conditions

Performances of the gloves are guaranteed up to 5 cleaning cycles under the conditions described above:Use of a household or industrial washing machine and a standard liquid detergent, synthetic program temperature 60 ° C and spin drying at 400 rotations per minute. Improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels

Drying conditions

Trumble drying at 60°C maximum Put the gloves on dry, clean hands. Ensure the inside of the gloves is dry before putting them on again.

Food contact US

FDA 21CFR 177.2600

LEGISLATION

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council. This product does not contain more than 0.1% of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH)

• CE-Type Examination Certificate

0075/014/162/04/14/0344

• Issued by the notified body nr

0075

CTC - 4 rue Hermann FENKEL - F 69367 LYON CEDEX 07

