



PRODUCT NUMBER: 2299400

C&G DeepTri1

Handling in oily or greasy conditions. Outdoor handling in wet environment. Assembly work in greasy/oily environment.

Honeywell

Overview

Reference Number

2299400

Product Type

Gloves

Range

General purpose

Line

Heavy handling

Brand

Honeywell

Industry

- Industry
- Automotive and Part Manufacturer
- Logistics
- Maintenance
- Mining and Quarrying
- Offshore
- Transportation

Product Use

Handling in oily or greasy conditions. Outdoor handling in wet environment. Assembly work in greasy/oily environment.

Features & Benefits

Feature

- Black polyamide knitted glove
- Fully dipped black foam nitrile coating.
- PVC dots on palm
- Elasticated knitted wrist.
- Gauge 13.
- Length : 25 cm

Benefit

COMFORT

The ergonomics seamless knit construction conforms better to the natural shape of the hand for greater strength and durability, superior confort

The filament yarn reduce linting for the most sensitive applications and easily laundered for extended use.

The tight knit gives the glove perfect support, limits the penetration of dirt and offers a good touch.

The foam coating optimise the glove's breathability.

The nitrile foam and PVC dots on palm improves the grip.

The knitted and elasticated wrist gives the glove good support.

RESISTANCE

The nitrile coating provides outstanding abrasion resistance and impermeability to oils. HYGIENE
The black colour is suitable for work in a soiled atmosphere.

Technical Description

Description

CE CATEGORY : II Intermediary risks

In accordance with standards :

EN 420-2003 Basic standards

EN 388-2003 Mechanical hazards

CHARACTERISTICS :

Black polyamide knitted glove

Fully dipped black foam nitrile coating.

PVC dots on palm

Elasticated knitted wrist.

Gauge 13.

Length : 25 cm

Product Technology

Knitted Coated

Gauge

13

Glove/liner color

Black

Coating Type

nitrile foam

Coating Color

Black

Length

25 cm

Harmlessness

In conformity with the European standards

Dexterity

Class 5

Sizes

7 to 11

EN 388 - Mechanical Hazards Abrasion Resistance

| | |
|---------------------|---|
| Abrasion resistance | 4 |
| Cutting resistance | 1 |
| Tear resistance | 2 |
| Puncture resistance | 1 |

Packaging Label

Tagging

CE HONEYWELL

2299400 XX

EN 420

EN 388 : 4121

Certifications

 E.C. Declaration of Conformity

EC Category PPE

2

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

0075/797/162/08/14/0749 EXT 01/08/14

EC Attestation

 EC Attestation

EC Attestation Number

0075/797/162/08/14/0749 EXT 01/08/14

Additional Information

User Manual

UI 102

User Information Sheet

102

Maintenance

Storage Information

Minimum packaging : 10 pairs.

Cartons of 100 pairs.

Care Instructions

This article can be cleaned. For cleaning instructions, please contact Honeywell Safety Products.