

**GENERAL DATA****Division :** Body Protection**Family :** Protective Gloves**Range :** Thermal Protection**Line :** Heat**Brand formerly known as :** PERFECT FIT**Business Countries**

EMEA

United Kingdom

Middle East

Activity Domains :Glass Industries • Iron and steel industry • Industry •
Automotive and Part Manufacturer**Product Use :**

For handling of sharp and hot objects in a dry atmosphere. Glass industry and paper. Automobiles, car equipment manufacturers.

PRODUCT ADVANTAGES**Feature :**

100 % KEVLAR knitted glove.

Lined with 100% cotton knitted glove.

150 mm green fireproofed canvas cuff.

Ambidextrous.

Gauge 7.

Length 37 cm.

Benefit :**Comfort**

The knitting technique helps to obtain a glove that conforms snugly to the hand and good dexterity. The glove offers maximum comfort and added sturdiness.

Kevlar glove lined with a cotton glove, pleasant to the touch.

The reinforced lining enhances the glove's mechanical performance while absorbing perspiration.

It is ambidextrous and thus more cost-effective.

The glove's relative thickness (gauge 7) helps to absorb shocks, making it suitable for the handling of heavy objects.

Resistance

The Kevlar fibre offers good resistance to cuts and protection against thermal hazards (contact heat).

Glove endowed with a fire retardant canvas (150mm), thus extending protection of the forearm.

Withstands 18.5 seconds at 250C and 13.3 seconds at 350C

TECHNICAL DESCRIPTION

Description :

100 % KEVLAR® knitted glove.
Lined with 100% cotton knitted glove.
150 mm green fireproofed canvas cuff.
Ambidextrous.

SIZE	WIDTH (+/- 5 mm)	LENGTH (+/- 10 mm)
9	130 mm	135 mm

Product Technology :

Knitted

Gauge :

7

Length :

37

Harmlessness :

In conformity with the European standards.

Dexterity :

Class 1

Size :

9

EN 388 - Mechanical hazards

Abrasion resistance : 2
Cutting resistance : O
Tear resistance : X
Perforation resistance : X

EN 407 - Heat and/or fire

Behaviour and/or fire : X
Resistance to contact heat : 2
Resistance to convective heat : X
Resistance to radiant heat : X
Resistance to small metal splashes : X
Resistance to molten metal splashes : X

ADDITIONAL INFORMATION

Care Instruction :

In order to keep its properties, this article should not be cleaned.

User manual number :

069

CERTIFICATION AND CONFORMITY

European Directives :

89/686/EEC

EC Category PPE* : Category II**Standards :**

EN 420 / EN 388 / EN 407

Tagging :

CE PERFECT FIT
20 326 81 9
EN 388 : 25XX
EN 407 : X2XXXX

EC Attestation Number :

0479/89/94

Laboratory :

DUPONT

*PPE : Personal Protective Equipment

EC CONFORMITY DECLARATION

The manufacturer or its legal representative supplier settled in the European Community:

Sperian Protection Europe

Declares that the next Personal Protective Equipment described here after is in conformity with the provisions of Council Directive 89/686/CEE:

Designation: ARATHERMA COMFORT

Reference: 2032681

Standard(s): EN 420 EN 388 EN 407

This PPE is the object of the above EC attestation type:

0479/89/94

Delivered by:

DUPONT

PO Box 15

BT47 1TU LONDONDERRY

Northern Ireland

Made at Roissy, on the 06/06/2007

By:

Division: Body Protection

