

TECHNICAL SPECIFICATION



Stealth™ 8000

Indoor/Outdoor Anti Scratch HC Lens / ASA790-162-900



DESCRIPTION

A lightweight safety spectacle, weighing just 26g, the wraparound 9 base curve polycarbonate lens has a built in adjustable PVC nosepiece for added comfort and stability. Low profile tension control temples provide extra grip. Temple tips feature spectacle cord attachment points. UVA, UVB and UVC protection.

OPTIONS

Amber K Rated (ASA790-161-200)

Clear Anti-mist / Anti-scratch Lens (ASA790-151-300)

Clear K & N AS/AF Rated (ASA790-1A1-300)

Clear K Rated (ASA790-161-300)

Indoor/Outdoor Anti Scratch HC Lens (ASA790-162-900)

LED Clear Anti-mist Lens (ASA106-121-300)

Smoke K Rated (ASA790-166-400)

SAFETY STANDARDS

EN 172 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 12 Jun 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



SPECIFICATIONS



Product Weight
26g



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.7



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
5



Manufacturer's Trademark
JSP Dagger



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °
Maximum protection for glasses
F

FEATURES



Comfort & Grip

Built-in soft rubber provides both comfort and grip to the side of the head to keep them secure without irritation.



Spectacle Cord Anchor

The temple tips have a spectacle cord anchor point for further practicality, preventing loss or scratching from being put on rough surfaces.



Comfortable Nose Bridge

Built-in adjustable PVC nose piece for added comfort and stability. It flexes and adjusts to fit the shape of the nose.

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Aerospace

Agricultural

Airports

Facilities Management

Food and Drink Manufacturing

Law Enforcement

Manufacturing

Maritime

Rail and Tunnelling

Renewable, Wind and Solar Energy

Scaffolding and Roofing

Sole Trader

Utilities Contractors

RANGE

**STEALTH
8000**

DOWNLOADS

[Image Pack \(ZIP\)](#)

[doc-stealth-8000-spectacles.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 12 Jun 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

