

PRO2000 FILTERS

TECHNICAL INFORMATION

PRO2000 GF 32 AX

(GAS FILTER, VOLUME 320 ml)

Colour code:

brown



Ref.Nr	Packing	EN standard	CE mark	Certificate N°	Date
042970	20 pcs	EN 14387:2004	CE 0121 BIA	961102	17.11.2004

Gas filter GF 32 AX protects against:

AX = Gases and vapours from organic compounds with a boiling point below 65 °C.

Limitations of use: see Scott Health & Safety instructions for use of AX-filters.

AX-filter is recommended for single use only (EN 14398).

TECHNICAL DATA

Feature	GF 32 AX result	EN 14387 requirement
Weight	268 g	max 500 g with a full face mask max 300 g with a half mask
Breathing resistance		
30 l/min	1.07 mbar	1.40 mbar
95 l/min	3.7 mbar	5.60 mbar
Filter capacity @ 30 l/min. Test gases/concentration vol%. Min permitted breakthrough time (with negative pressure respirators)		
Dimethylether CH ₃ -O-CH ₃ [0,05 vol%]	79 min	min 50 min
Isobutane C ₄ H ₁₀ , [0,25 vol%]	65 min	min 50 min
Dimensions		
Height	75 mm	
Diameter	110 mm	
Volume	320 ml	
Thread	40 mm	EN148-1
Other data		
Casing material	Reinforced polypropylene	
Storage time	5 years (factory sealed)	
Temperature (Storage)	-10...+50 °C (factory sealed)	

Limitations of use: see Scott Health & Safety instructions for use of AX-filters.