



Bilsom Technology

GENERAL DATA

Division : Head Protection
Family : Hearing Protection
Range : Earmuffs
Line : Noise Blocking Earmuffs
Brand formerly known as : BILSOM

Business Countries

EMEA
 United Kingdom
 Middle East

Activity Domains :

Agriculture • Army - Defence • ATEX environment •
 Automotive and Part Manufacturer • Aviation • Building
 and Construction • Catering • Chemical Industries •
 Energy or Electricity • Fire Protection brigades • Fishing
 • Food Industries • Foundry • Glass Industries • Green
 Spaces • Homeland defense • Industrial Cleaning • Iron
 and steel industry • Logistics • Maintenance • Medical
 and Pharmaceutical • Metal steel • Mining and Quarrying
 • Offshore • Paper Industries • Petro-chemical •
 Printing Industries • Services • Telecoms • Textile
 Industries • Transportation • Utilities • Water treatment
 • Welding • Wood Industries • Laboratory • Ship
 Building • Industry • Administration



Product Use :

Noise Blocking Earmuff

PRODUCT ADVANTAGES

Feature :

AIR FLOW CONTROL TECHNOLOGY

Bilsom's patented Air Flow Control™ technology delivers optimal attenuation across all frequencies, without increasing earcup size or weight. A patented baseplate chamber and high-tech non-woven layer manage the flow of air inside the earmuff to control how sound reaches the ear. The result is better, more consistent overall attenuation for virtually all industrial noise environments.

STEEL WIRE CONSTRUCTION

Robust steel wire band withstands demanding use, especially in tough environments.

SNAP-IN EAR CUSHIONS

Snap-in ear cushions make replacement quick and easy.

NECKBAND STYLE

Sleek, anatomic behind-the-head design can be worn with other PPE including face shields, helmets, visors and respirators. Includes headband strap for better positioning on the head.

Benefit :

When you're in a tough industrial environment and need to block noise, Bilsom's Leightning series' steel wire construction provides high performance and robust durability. Leightning stands up to daily use and abuse without compromising comfort. Bilsom has optimized the Leightning series to deliver the highest level of comfort available.

TECHNICAL DESCRIPTION

SNR (dB) : 29

H (dB) : 31

M (dB) : 27

L (dB) : 21

Attenuation Data :

| Frequency (Hz) Frequenz (Hz) Fréquence (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|---|------|------|------|------|------|------|------|------|
| Mean Attenuation (dB) Mittlere Dämmung (dB) Atténuation moyenne (dB) | 18.3 | 17.9 | 21.9 | 27.9 | 32.7 | 32.1 | 35.4 | 35.8 |
| Standard Deviation (dB) Standardabweichung (dB) Déviation standard (dB) | 5.5 | 3.5 | 3.2 | 3.0 | 2.9 | 2.9 | 3.5 | 3.8 |
| Assumed Protection (dB) Angenommener (dB) Protection supposée (dB) | 12.8 | 14.4 | 18.7 | 24.9 | 29.8 | 29.2 | 31.9 | 32.0 |

Earmuff Construction :

Metal

Other Material :

Steel Wire, PC/PBT, ABS, PUR-E, PVC, LDPE

Dielectric : No

Color :

Black and Light Grey

Batteries Needed :

None

Weight (grs) :

171

Design Patents :

Air Flow Control™

Headband Style :

Neckband

Sound Amplification : No

AM/FM Radio : No

Automatic Shut-Off Function : No

Audio Input Jack : No

Hi-Visibility : No

ADDITIONAL INFORMATION

Accessories :

Hygiene Kit - Packed in a plastic bag, including two ear cushions and two foam pads. Ref. # 1011998 for L1, L1H, L1N

Cool II Pads - Sweat absorbing pads. Ref. # 1000365 5-pair, Ref. # 1000364 100-pair

Optisorb - cotton sleeve slides over earcup. Ref. # 3302101

Polar Hood - Ref. # 1016870 Lg/XLg; Ref. # 1016871 Sm/Med

Life Cycle :

Cushions should be replaced periodically to retain maximum attenuation. Use the following as a guideline for replacement of ear cushions and insert foam. General use and wear - Ear cushions and foam inserts should be replaced at least every 6 months. Heavy use or wear in humid/extreme climates - Ear cushions and foam inserts should be replaced at least every 3 months. Cracking or leakage is visible - replace ear cushions and foam inserts immediately.

Storage Information :

When not in use, the earmuffs should be stored in a clean dry container or locker. Do not use solvents or petroleum-based products. Do not immerse the earmuffs in water.

Care Instruction :

Earmuffs are an important safety product and should be inspected regularly. Its use, care and maintenance are critical to its effective performance. Earmuffs and in particular ear cushions may deteriorate with use and should be examined at frequent intervals for cracking and leakage. If the ear cushions become hard, damaged or deteriorated, they should be replaced promptly using recommended Hygiene Kits. Earmuffs should be maintained by regular cleaning. Use a mild disinfectant solution. A gentle wipe is all that is required.

User manual number :

90010506

EAN Code :

7312550119945

CERTIFICATION AND CONFORMITY**European Directives :**

89/686/EEC

EC Category PPE* : Category II**Standards :**

EN-352-1:2002

Quality Assurance :

ISO 9001 / 2000

EC Certification Number :

EC1288

EC Attestation Number :

041046

Laboratory :

INSPEC

*PPE : Personal Protective Equipment

EC CONFORMITY DECLARATION

The manufacturer or its legal representative supplier settled in the European Community:
Howard Leight by Sperian

Declares that the next Personal Protective Equipment described here after is in conformity with the provisions of Council Directive 89/686/CEE:

Designation: Leightning L1Ns Neckband Earmuff
Reference: 1011994
Standard(s): EN-352-1:2002

This PPE is the object of the above EC attestation type:
041046

Delivered by:

INSPEC
56 Leslie Hough Way
Salford
M6 6AJ Greater Manchester
United Kingdom

Made at Sweden, on the 12/17/2004

By:

Division: Head Protection



EC TYPE-EXAMINATION CERTIFICATE :1288

Product description:-

Ear-muffs

Product identification:-

Bilsom Leightning L1Ns

Manufactured by:-

Bacou-Dalloz AB
Dungattan 2
260 50 Billesholm
Sweden

When assessed and examined against harmonised standard EN352-1:2002 is found to be in conformity with Council Directive 89/686/EEC, and associated amendments, relating to personal protective equipment .

Signed

K J Warren, Manager, Certification Services

Date: 17th December 2004

For and on behalf of INSPEC International Ltd. (Notified Body No: 0194)

For terms and conditions of issue, see page 2

certificate invalid
if not embossed

Terms and Conditions associated with INSPEC
EC Type-Examination Certificate No: 1288

Reference Documents:-

- | | | | |
|------|--------------------------|---|--|
| i) | Test Reports | - | INSPEC 04.10.46 |
| ii) | Technical File | - | INSPEC ref. TF/1288 |
| iii) | Test and Inspection Plan | - | CE Product Certification, Test and Inspection Plan |

Conditions attached to the issue of this certificate:

- i) Marking and instructions have been assessed in the English language only. It is the Manufacturers/Authorised Representatives responsibility to obtain and supply language versions acceptable to the country where the product is to be sold.
- ii) Any changes to the product, technical file or quality manual/quality plan shall be immediately notified to INSPEC.
- iii) The Manufacturer/Authorised Representative shall comply at all times with INSPEC's Regulations governing CE Product Certification.
- iv) This Certificate remains the property of INSPEC and may be withdrawn if any of the conditions attached to its issue are not complied with.

CERTIFICATION SCHEDULE

COMPANY: Bacou-Dalloz AB

CERTIFICATE NO: EC1288

SCHEDULE NO: ONE

DATE: 17th December 2004

Model: Bilsom Leightning L1Ns

Description: Behind the neck ear-muff

Size Range: S / M / L

Attenuation Data

| | | | | | | | | |
|----------------|----------|------|----------|------|----------|------|------------|------|
| Freq. (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
| Mean att. (dB) | 18.3 | 17.9 | 21.9 | 27.9 | 32.7 | 32.1 | 35.4 | 35.8 |
| Std. Dev. (dB) | 5.5 | 3.5 | 3.2 | 3.0 | 2.9 | 2.9 | 3.5 | 3.8 |
| APV (dB) | 12.8 | 14.4 | 18.7 | 24.9 | 29.8 | 29.2 | 31.9 | 32.0 |
| | H = 31dB | | M = 27dB | | L = 21dB | | SNR = 29dB | |

Signed for and on behalf of INSPEC.....

Kevin Warren, Manager, Certification Services