

## The Powered Scaffold Tower

With a large work platform (1520 x 750 mm), the Power Tower gives the user more room to work and more room for tools and equipment, in fact more than 50% larger than its nearest competitor.

The Power Tower requires less operations to cover the same area for many applications. And at only 780 mm wide will still pass comfortably through a standard single doorway.

The heavy duty Power Tower really is the cost effective, safe and efficient alternative to large podiums or small scaffold towers.

**Typical applications and users:** For users who want larger platform size for themselves, tools and equipment. Typically dry-lining, pipe and duct work, air-conditioning, general M & E contractors, shop-fitters, retail refit etc.

### Key Features

- 3.1 m platform height, 5.1 m working height
- 250 kg safe working load (1 person)
- Compact - only 0.78 m wide, passes easily through standard doorways
- Large 1.52 x 0.75 m platform size
- Only 0.78 x 1.6 m working footprint
- Easy access gate

### **PUSH AROUND**

Indoor use

Working Height: 5.1 m

Applications: Dry-lining. Pipe & Ductwork. Air conditioning. M&E. Shopfitting. Retail.



# Model POWERTOWER®

LOW-LEVEL ACCESS

## Specifications

### OPERATING DIMENSIONS

Maximum working height:	5.10 m
Maximum platform height:	3.10 m
Platform dimensions:	1.52 m x 0.75 m
Working foot print:	1.60 m x 0.78 m
Safe working load:	250 kg

### CLOSED DIMENSIONS

Length:	1.60 m
Width:	0.78 m
Height:	1.85 m
Weight:	342 kg

### POWER OPTIONS

Battery:	12V c/w automatic charger.
Mains:	110V or 230V.
Controls:	Simple push button basket controls.

### OTHER FEATURES

Construction:	Heavy duty fabricated steel superstructure, stainless steel bushed pivots, tough powder coated finish.
Safety:	CE marked, complies with applicable European legislation including the Machinery Directive using the EN280 design standard. Full fail-safe hydraulics, automatic locking wheels.
Options:	Tilt alarm c/w auto cut-out. Narrow basket for suspended ceiling grid access. Pipe Carrying kit (max 2" pipe). Tool tray. Foam buffer kit.

## Safety features

- Fail-safe hydraulic circuit complete with check valve on lift cylinder
- Improved heavy-duty Auto-Lok wheels on elevation provide secure base
- Emergency descent from ground level
- Audible ascent and descent drive alarm



## IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

# JLG®

## JLG EMEA BV

Polaris Avenue 63  
2132 JH Hoofddorp  
The Netherlands  
Phone: +31 (0)23 565 5665  
[www.jlg.com](http://www.jlg.com)

An Oshkosh Corporation Company